

HONDA

The Power of Dreams

Models	CRF250RX CRF250RX
GENERAL	
Warranty	None
Service Intervals	As per owners manual
0 - 100 km/h (sec)	-
DIMENSIONS AND WEIGHTS	
Claimed KERB Weight	108
Length (mm)	2176
Width (mm)	839
Height (mm)	1281
Seat height (mm)	964
Rake/Trail (°/mm)	114
Wheel Base	1477
DRIVE	
Drive	Chain
Front Suspension	49mm Showa (Hitachi Astemo, Ltd) coil-spring USD fork
Rear Suspension	Showa (Hitachi Astemo, Ltd.) Mono shock with Honda Pro-Link
ENGINE	
Tank Capacity (l)	8
Starter	Electric
Engine Configuration	Liquid-cooled 4-stroke single DOHC
Cylinders	1
Valves per Cylinder	4
Capacity	249.4
Power (KW)	-
Torque (NM)	-
Gearbox	5-spd
SAFETY	
Brakes	(F)260mm hydraulic wave disc (R)240mm hydraulic wave disc
STYLING	
Frame Material	Aluminium twin tube
WHEELS	
Tyres Front	90/90-21 Dunlop AT81
Tyres Rear	110/100-18 Dunlop AT81
Wheels	Aluminium spoke
STANDARD AVAILABLE ACCESSORIES	
Luggage	-
Maintenance	-
Comfort	-
Utility	-

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.